




## UX10 FULLY RUGGED TABLET

- 12세대 Intel® Core™ i5/i7 프로세서
- 10.1" FHD Lumibond® display with Getac sunlight readable technology (1,000 nits) and capacitive touchscreen.
- Enhanced enterprise security with optional Intel® vPro®, Windows Hello face-authentication camera and multifactor authentication options.
- Versatile I/Os connectivity including Thunderbolt™ 4.
- Enhanced Wi-Fi, GPS and LTE performance.



UX10 3D Demo



SPECIFICATIONS

Generation  
G3

운영체제  
Windows 11 Pro

CPU  
Intel® Core™ i5-1235U Processor  
Max. 4.4GHz with Intel® Turbo Boost Technology  
- 12MB Intel® Smart Cache

Platform options  
Intel® Core™ i5-1245U vPro® Processor  
Max. 4.4GHz with Intel® Turbo Boost Technology  
- 12MB Intel® Smart Cache

Intel® Core™ i7-1255U Processor  
Max. 4.7GHz with Intel® Turbo Boost Technology  
- 12MB Intel® Smart Cache

Intel® Core™ i7-1265U vPro® Processor  
Max. 4.8GHz with Intel® Turbo Boost Technology  
- 12MB Intel® Smart Cache

Intel® Pentium™ 8505 Processor  
Max. 4.4GHz with Intel® Turbo Boost Technology  
- 8MB Intel® Smart Cache

그래픽 컨트롤러  
Intel® UHD Graphics

디스플레이  
10.1" Wide Viewing Angle TFT LCD WUXGA (1920 x 1200)  
Protection film  
1,000 nits LumiBond® display with Getac sunlight readable technology  
Capacitive multi-touch screen

스토리지 & 메모리  
8GB DDR4  
옵션: 16GB / 32GB DDR4

256GB PCIe NVMe SSD  
옵션: 512GB / 1TB PCIe NVMe SSD

키보드  
Power button  
5 tablet programmable buttons

포인팅 장치  
Touchscreen  
- Capacitive multi-touch screen  
- 옵션: Dual mode touchscreen (multi-touch and digitizer)

확장 슬롯  
옵션 (top side): 1D/2D imager barcode reader, or Serial port, or USB 3.2 Gen 1 Type-A port, or LAN port (RJ45) , or microSD or HF RFID reader<sup>i</sup>, or HDMI 2.0<sup>ii</sup>  
옵션 (right side): LAN port (RJ45) or Fingerprint reader<sup>iii</sup>  
옵션 (back side): Smart card reader, or Bridge battery, or Bridge battery + Smart card reader<sup>iv</sup>

I/O 인터페이스  
FHD webcam x 1<sup>v</sup>  
8M pixels auto focus rear camera x 1  
Audio in/out combo x 1  
DC in Jack x 1  
USB 3.2 Gen 2 Type-A x 1  
Docking connector x 1  
Thunderbolt™ 4 Type-C x 1  
옵션: Windows Hello face-authentication camera (front-facing) x 1<sup>v</sup>  
옵션: RF antenna pass-through for GPS, WWAN and WLAN

통신 인터페이스  
옵션: 10/100/1000 base-T Ethernet  
Intel® Wi-Fi 6E AX211, 802.11ax  
Bluetooth (v5.3)<sup>vi</sup>  
옵션: Dedicated GPS with L1/L5<sup>ix</sup>  
옵션: 4G LTE mobile broadband with integrated GPS<sup>vii, viii, ix, x</sup>  
옵션: 5G Sub-6 with integrated GPS<sup>vii, viii, ix</sup>  
Dual SIM (Micro-SIM 3FF and e-SIM)<sup>vii, viii</sup>

보안 기능  
TPM 2.0  
Kensington lock  
옵션: Intel® vPro® Technology  
옵션: HF RFID reader<sup>li</sup>  
옵션: Fingerprint reader<sup>iii</sup>  
옵션: Smart card reader<sup>iv</sup>  
옵션: Windows Hello face-authentication camera (front-facing)<sup>v</sup>

전원  
AC adapter (65W, 100-240VAC, 50/60 Hz)  
Li-ion battery (11.1V, typical 4200mAh; min. 4080mAh) x 1  
옵션: High capacity Li-ion battery (10.8V, 9240mAh) x 1  
옵션: Bridge battery<sup>iv</sup>

치수 & 무게  
279 x 194.5 x 23.5mm (10.98" x 7.65" x 0.92")<sup>xi</sup>  
1.22kg (2.68lbs)<sup>xi</sup>

견고성  
MIL-STD-810H certified  
IP66 certified  
MIL-STD-461G certified<sup>xii</sup>  
Vibration & 6ft (1.8m) drop resistant<sup>xiii</sup>  
옵션: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D)<sup>xiv</sup>

사용가능 환경  
Temperature<sup>xv</sup>:  
- Operating: -29°C to 63°C / -20°F to 145°F  
- Storage: -51°C to 71°C / -60°F to 160°F  
Humidity:  
- 95% RH, non-condensing

소프트웨어  
Getac Utility  
Getac Camera  
Getac Geolocation  
Getac Barcode Manager<sup>xvi</sup>  
Getac Driving Safety Utility (trial version)  
Getac KeyWedge Barcode Reader Utility (trial version)  
옵션: Absolute Persistence®

옵션 소프트웨어  
Getac Driving Safety Utility  
Getac KeyWedge Barcode Reader Utility  
Getac Device Monitoring System (GDMS)  
Getac VGPS Utility<sup>xvii</sup>

악세서리  
Battery (11.1V, typical 4200mAh; min. 4080mAh)  
AC adapter (65W, 100-240VAC)  
Capacitive stylus with tether

옵션:  
Carry bag  
Folio case  
Battery (11.1V, typical 4200mAh; min. 4080mAh)  
High capacity Li-ion battery (10.8V, 9240 mAh)  
Multi-Bay charger (Dual-Bay)  
Multi-Bay charger (Eight-Bay)  
AC adapter (65W, 100-240VAC)  
AC adapter (90W, 100-240VAC)  
MIL-STD-461 AC adapter (90W, 100-240VAC)  
DC-DC vehicle adapter (120W, 11-32VDC)  
Digitizer pen  
Capacitive stylus with tether  
Protection film  
Hard handle  
Rotating hand strap with kickstand  
Shoulder strap (2-point)  
Shoulder harness (4-point; handsfree)  
Detachable keyboard  
Vehicle cradle<sup>xviii</sup>  
Keyboard dock<sup>xviii</sup>  
Vehicle dock<sup>xviii</sup>  
Office dock  
100W Type-C adapter

UX10 FULLY  
RUGGED TABLET

- I. 13.56MHz contactless HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- II. 1D/2D imager barcode reader, Serial port, USB 3.2 Gen 1 Type-A port, LAN port (RJ45), HF RFID reader, MicroSD and HDMI 2.0 are mutually exclusive options.
- III. Fingerprint reader and LAN Port are mutually exclusive options.
- IV. Smart card reader, Bridge battery and Bridge battery + Smart card reader are mutually exclusive options.
- V. FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options.
- VI. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- VII. One physical SIM card slot and one eSIM.
- VIII. Network service may vary depending on local telecommunication providers.
- IX. Supports GPS, GLONASS, Galileo, BeiDou and QZSS. Only available in US, UK, EU, Australia and New Zealand.
- X. Units with 4G LTE option come with an embedded SIM card slot.
- XI. Weight and dimensions vary from configurations and optional accessories.
- XII. MIL-STD-461 90W AC adapter sold separately.
- XIII. Drop test results vary from configurations and optional accessories.
- XIV. Available with limited configurations and environment conditions.
- XV. Tested by an independent third-party test lab following MIL-STD-810H.
- XVI. Available when barcode reader option is selected.
- XVII. Models require either embedded or standalone GPS module.
- XVIII. Gamber Johnson and Havis vehicle docks are e-mark certified.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

Vehicle Dock		Office Dock
Serial Port	1	1
External VGA	-	1
Microphone	-	1
Audio Output	-	1
DC in Jack	1	1
USB	USB 2.0 x 2 USB 3.2 Gen 1 x 2	USB 2.0 x 2 USB 3.2 Gen 1 x 2
LAN	1	1
HDMI 1.4	-	1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	-
Kensington Lock	1	1



(주)씨에스글로비즈  
경기도 과천시 과천대로7길 65, 과천상상자이타워 B동 1220호  
제품 문의 : 02)782-4700 / 기술 문의 : 02)782-7500  
www.getac.co.kr / getac\_sales@getac.co.kr